

4" Floating Adjustable Eyeball Downlight with 5-CCT Switch

The innovative 4" Floating Eyeball offers 360° rotation and a 90° tilt range for added versatility.




Features

- 9W / 780 lm
- IC Rated for direct contact to insulation
- CRI 90+
- 120V
- ETL Listed for damp locations
- CA Title 24 compliant
- Dimmable Triac/ELV

Specifications

Wattage	9W
Lumens	780 lm
Voltage	120V
Color Temp.	2700K, 3000K, 3500K, 4000K, 5000K
Dimmable	Triac/ELV
Lamp Type	LED
CRI	90+
Damp Location	Listed

Options



Technical Details

Optics: Polycarbonate lens diffuses light evenly throughout space with no LED pixelation.

Construction: Aluminum die-cast trim with durable powdercoat finish. Plenum rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two 7/8" knockouts with slots for pryout.

Installation: Designed for super shallow ceiling plenums without any housing. High strength steel spring clip for easy installation. Hole cut out template for proper trim installation.

Electrical: Included driver connects directly to 120V power supply. Standard input wattage is 9W, 85 lumens per watt. Replaces 75W incandescent.


Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the ELM System Dimmer Compatibility List.

Listings: ETL Listed for Damp Locations. IC-Rated for direct contact with insulation. Air Tight certified in accordance with ASTM E283-2004. California Title 24 Compliant (JA8-2016-E)

Warranty: 5-year limited warranty.



Dimensions



Product Number

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
ERT416CT5W	LED	780 lm	2700K, 3000K, 3500K, 4000K, 5000K	9W	120V	Triac/ELV	White

Product Number Builder Example: ERT416CT5W


4" Floating Adjustable Eyeball	Color Temp	Finish
ERT416	CT5 2700K - 5000K	W White BZ Bronze B Black

Compatible Products

For use with 4" Elm™ System Slim Panels



4" Elm™ New Construction Frames



Frame with Hanger Bars
New Construction

CAT NO.	SPECIFICATIONS
E4LF1 (4" Round)	8 1/2" L x 6" W x 4 1/4" Opening



Round Mounting Plate
New Construction

CAT NO.	SPECIFICATIONS
EMP4 (4" Round)	13 1/4" L x 6 1/4" W x 4 3/8" Opening



Universal Frame for 2", 4" and 6" Downlights
New Construction

CAT NO.	SPECIFICATIONS
E246LF1	12 1/8" L x 7 5/8" W