

# Darby LED Standard Lumen Decorative Flush Mount Lights




## Features

- White polycarbonate lens.
- Contemporary double ring design.
- Fully assembled and easy to install.
- Suitable for qualified hard wire installation into a standard 4x4 junction box.
- UL listed for damp location.
- ENERGY STAR. CA Title 24 compliant (JA8-2016).

## Specifications

|                             |                                   |
|-----------------------------|-----------------------------------|
| <b>Wattage</b>              | 25W                               |
| <b>Lumens</b>               | 1700 lm                           |
| <b>Voltage</b>              | 120/277V                          |
| <b>Color Temp.</b>          | 2700K, 3000K, 3500K, 4000K, 5000K |
| <b>Dimmable</b>             | Triac/ELV                         |
| <b>Lamp Type</b>            | LED                               |
| <b>CRI</b>                  | 90+                               |
| <b>Damp Location Listed</b> |                                   |

## Size Chart



| Size | Diameter | Height |
|------|----------|--------|
| 10"  | 9 7/8"   | 2 3/4" |
| 12"  | 12 1/8"  | 3 3/8" |
| 14"  | 14 1/8"  | 3 3/4" |
| 16"  | 16 1/8"  | 4 3/8" |
| 18"  | 18 1/8"  | 4 3/4" |

## Product Number

| Item      | Description | Lamp type | Lumens  | CCT                               | Watts | Voltage  | Dimming   | Finish |
|-----------|-------------|-----------|---------|-----------------------------------|-------|----------|-----------|--------|
| ELD14CT5W | 14"         | LED       | 1700 lm | 2700K, 3000K, 3500K, 4000K, 5000K | 25W   | 120/277V | Triac/ELV | Nickel |

## Product Number Builder Example: ELD11030W

| ELCO LED Flush Mount | Diameter | Color Temp.    | Finish   |
|----------------------|----------|----------------|----------|
| <b>ELD1</b>          |          |                |          |
|                      | 10 10"   | 30 3000K       | W Nickel |
|                      | 12 12"   | 40 4000K       |          |
|                      | 14 14"   | CT5 2700-5000K |          |
|                      | 16 16"   |                |          |