

Flexa™ 6" Round Reflector for Koto™ Module

Mix and match any ring finish with any reflector finish



Features

- 2 Piece Flexa™ trims for maximum design flexibility.
- Convenient twist-lock design for ease of installation.
- Diecast construction for lasting quality.
- 7 3/8" O.D. - 2 1/4" H

Technical Details

Construction: Diecast aluminum with a powder coated finish.

Installation: Twist-lock design allows for easy mounting onto the Koto™ LED Module. Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Module: Koto™ LED Modules (ELK07 & ELK09 Series)

Lamp: Koto™ LED Module.

Options



All White



All Black



All Bronze



Black Reflector
w/White Ring



All Chrome



Chrome Reflector
w/White Ring




Chrome Reflector
w/Nickel Ring



Haze Reflector
w/White Ring

Dimensions



Product Number

Item	Finish
ELK610CW	Chrome Reflector w/White Ring

Product Number Builder

Example: **ELK610WW**


6" Koto™ Flexa™ Trim	Reflector Finish	Ring Finish
ELK610		
	W White B Black BZ Bronze C Chrome H Haze	W White B Black BZ Bronze C Chrome N Nickel

Compatible Products

For use with 6" Koto™ Twist-&-Lock Trims



Koto™ LED Module



Koto™ LED Module
ELK07 - ELK09

PRODUCT NUMBER BUILDER					
Koto™ LED Module	Lumens	Color Temperature	Beam Angle		
ELK					
07	750 lm	27 2700K	(blank)	38° lens (Standard)	
09	950 lm	30 3000K	-S	18° lens	
		35 3500K	-N	25° lens	
		40 4000K	-W	60° lens	
		SD Sunset Dimming (ELK09 Only)	-FC	18° - 50° Adjustable (ELK07 Only)	

ACCESSORIES



Lens

EP731C	18° Lens
EP732C	25° Lens
EP733C	38° Lens
EP734C	60° Lens

*EP732C, EP733C, EP734C Included



Reflectors

EP735C	15°
EP736C	25°
EP737C	38°
EP738C	60°



Secondary Optics

L45	Hex Louver
L46	Linear Lens
L47	Spread Louver
L49	Frosted Lens
L50	Color Shifter


Koto™ LED Module with 5-CCT Switch

CCT SWITCH


5 CCT

Product Number
ELK08CT5

6" Koto™ Dedicated LED ICA Housings



6" Standard ICA Housing
New Construction



6" Standard Remodel ICA Housing
Remodel



2-Hour Fire Rated 6" ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
EL770ICA	7 1/2" Height
EL760ICA	5 1/2" Height, Shallow

CAT NO.	SPECIFICATIONS
EL770RICA	7 1/2" Height
EL760RICA	5 1/2" Height, Shallow


CAT NO.	SPECIFICATIONS
EL76FICA	7 3/4" Height - Sound Rated
EL75FICAS	6 3/16" Height, Shallow

Compatible Products

For use with 6" Koto™ Twist-&-Lock Trims



Koto™ Architectural LED Light Engine



Koto™ LED Light Engine
ELK19 - ELK21

PRODUCT NUMBER BUILDER				
Koto™ LED Light Engine	Lumens	Color Temperature	Beam Angle	
ELK				
19	750 - 850 lm	27D 2700K	(blank)	38° lens (Standard)
21	1100 - 1500 lm	30D 3000K	-S	18° lens
		35D 3500K	-N	25° lens
		40D 4000K	-W	60° lens
		SD Sunset Dimming (ELK19 Only)	-FC	18° - 50° Adjustable (ELK21 Only)

ACCESSORIES



Lens

EP731C	18° Lens
EP732C	25° Lens
EP733C	38° Lens
EP734C	60° Lens

**EP732C, EP733C, EP734C Included*

Reflectors

EP735C	15°
EP736C	25°
EP737C	38°
EP738C	60°



Secondary Optics

L45	Hex Louver
L46	Linear Lens
L47	Spread Louver
L49	Frosted Lens
L50	Color Shifter

6" Koto™ Dedicated LED ICA Housings



6" Koto™ Maximum Adjustability ICA Housing
New Construction




6" Maximum Adjustability High Lumen ICA Housing
Double Wall

CAT NO.	SPECIFICATIONS
E6LK37ICA	7 1/2" Height, Triac/ELV, 850 (ELK19) - 1100 (ELK21) lm
E6LK38ICAD	7 1/2" Height, 0-10V/Triac/ELV, 850 (ELK19) - 1100 (ELK21) lm

CAT NO.	SPECIFICATIONS
E6LK43ICA	7 1/4" Height, 120V, Triac/ELV, 1250 lm
E6LK44ICAD	7 1/4" Height, 120/277V, 0-10V/Triac/ELV, 1250 lm
E6LK56ICA	7 1/4" Height, 120V, Triac/ELV, 1500 lm
E6LK57ICAD	7 1/4" Height, 120/277V, 0-10V/Triac/ELV, 1500 lm

12V AC Retrofit Koto™ LED Module



12V AC Retrofit
Koto™ LED Module
ELK08

PRODUCT NUMBER BUILDER				
Koto™ LED Module	Lumens	Color Temperature	Voltage	
ELK				
08	800 lm	27 2700K	-12	12V AC
		30 3000K		
		SD Sunset Dimming		

ACCESSORIES



Lens

EP731C	18° Lens
EP732C	25° Lens
EP733C	38° Lens
EP734C	60° Lens

**EP732C, EP733C, EP734C Included*

Reflectors

EP735C	15°
EP736C	25°
EP737C	38°
EP738C	60°

Secondary Optics

L45	Hex Louver
L46	Linear Lens
L47	Spread Louver
L49	Frosted Lens
L50	Color Shifter