



Project / Job Name:

Location:

Fixture Type:

Notes:

65-730 - 50 Watt LED DOB Tempered Glass Flood Light; 5000K CCT; Bronze Finish



GENERAL

Company	SATCO
EA Height	9.57
EA Width	9.65
EA Length	2.24
Bulb Included	Integrated
Material	Die-cast Aluminum
Fixture Type	Flood Light
Includes	Yoke Mount
Product Notes	NEMA Distribution: 6Vx6H (120x120)
Status	Active
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	<30%
Up Down Installation	Up
CCT Selectable	No
Wattage Selectable	No
Finish Family	Bronze
Amps	0.420A
Lens Finish	Clear
Lens Material	Tempered Glass
Lensed	Yes
Power Factor	>0.94
SDS Class	LED Fixture
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	250W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	30000
Beam Angle (degree)	120
Color Temp	Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-30C (-22F) to +45C (+113F)
Lumens	5750L
Volts	120v
Watts	50W

PHYSICAL

Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO

Warranty	3-Years
----------	---------

FEATURES

Flicker Free	No
--------------	----

PACKAGING

UPC	045923410963
Case Cube	1.6739
Case Height	10.39
Case Length	10.9
Case Quantity	10
Case UPC	10045923410960
Case Weight	21.3
Case Width	25.54
EA Cube	0.1197
EA Height	9.57
EA Length	2.24
EA Quantity	1
EA Weight	1.98
EA Width	9.65
Inner Cube	0.0
Pack Type	Color Box
Web Height	8.19
Web Width	7.15

COMPLIANCE

ADA Compliant	No
Bug Rating	B1-U2-G1
CA Prop 65	Lead
Dark Sky Rated	No
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Energy Star Certified	No
Title 20	Exempt
T24 Compliant	No