

Project Name

Location

Prepared By



SATCO S13180

13.5W/LED/HID/ED17/822/E26/CL

Notes

(www) 18-17-0025 01/20/20

General

Status	Active
Watts	13.5W
HID Equivalent	50W
Volts	120V-277V
Shape	ED17
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	2200K
Temperature	Warm White
CRI	80+
Lumens	1700L
Beam Spread	320
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 5.98 in. Width: 5.98 in. Height: 10.16 in.
Ballasting Requirements	Ballast Bypass

Electrical

Operating Frequency	60Hz
Power Factor	0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-30C (-22F) to +65C (+149F)

Physical

MOL	5.8
MOD	2.13
Housing Color	Frost
Weight (lb.)	0.17

Additional Information

Rated For Enclosed Fixture	Yes
IP Rating	IP65
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Wet
DLC Approved	No
California Status	Non-Compliant
Title 20 / 24 Status	Non-Compliant
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp